

# TDSmonitor

DM-2 / Industrial Dual TDS Monitor



## Specifications:

**Range:** 0-9990 ppm

**Accuracy:**  $\pm 2\%$

**Cable Length:** 46" (including sensor)

**Power Source:** 2 AAA Batteries (included)

**Battery Life:** Over 1000 Hours of Continuous Use

**Size:** 4.6 x 2.6 x .7in.

**Weight:** 201.3g / 7.1 oz.

## FEATURES:

*Highly efficient and accurate due to its advanced microprocessor technology.*

*Auto-Off function conserves battery power. The unit shuts off automatically after 20 seconds.*

*Dual Range - Measures from 0-999 ppm, with a resolution of 1 ppm. From 1000 to 9990 ppm, the resolution is in 10 ppm increments, indicated by a blinking 'x10' image.*

*Factory Calibrated: all meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated.*

*Comes equipped with 3/8" & 1/2" inch Quick Connect T-fittings for Merlin-Garden Pro™ or Tall Blue-Merlin™ for quick install.*

## USAGE:

*Measure the untreated water coming in vs. the purified water going out of your Reverse Osmosis system at any time.*

*Important for determining when the RO membranes need to be changed.*

*Always know how your system is performing. No more second guessing.*

**Limited 3 year warranty**

pure water's not **magic.**  
it's **logic.**

**HydroLogic™**  
PURIFICATION SYSTEMS